

# Safety-interlocked Reefer Outlet Product Selection Information

**R 3 2 - 4 8 0 - 3 0 - 2 2 S D - S P**

**R 3 2**

**4 8 0**

**Voltage**  
480 = 480VAC  
240 = 240VAC

**3 0**

**Circuit Breaker Trip Rating**  
30 = 30AMP  
50 = 50AMP  
60 = 60AMP

**2 2**

**Circuit Breaker Interrupting Capacity**  
22 = 22,000 AIC  
35 = 35,000 AIC  
65 = 65,000 AIC

**S**

**Faceplate Size**  
S = 5" X 6", L = 8" X 7", G = 9.5" X 8"  
N = 12" X 10.5", M = 10.5" X 10", X = 21" X 15"

**D**

**Receptacle Material**  
Blank = Lexan®  
SN = 316 Stainless Steel/Rynite Insert  
N = Polyamide/Rynite Insert

**D**

**Interlock Mechanism Model**  
C & D = Mechanically Interlocked  
E = Electrically Interlocked

**Optional Features**  
P = Pilot Light  
A = Auxiliary Contact  
R = Reverse Activated

**Receptacle Cover**  
SP = SS Snap Cover  
SW = Screw Cover  
FP = Flap Cover

**Receptacle Rating / Configuration**  
R32 = 32AMP IEC 60309 1&2 CEE17-3h Configuration  
R60 = 60AMP ISO Configuration  
R50 = 50AMP  
R30 = 30AMP

