

LEFT VIEW

FRONT VIEW

RIGHT VIEW

FRONT VIEW
(DOORS REMOVED)

FRONT VIEW
(DOORS & DEADFRONT REMOVED)


BOTTOM VIEW

ISOMETRIC VIEW

TABLE OF KAIC RATINGS

DISCONNECTS	SHORT CIRCUIT RATING
SWITCH	10 KA
CIRCUIT BREAKER	65KAIC@208VAC
	35KAIC@480VAC
	18KAIC@600VAC

- NOTES:
- COMPLETE ASSEMBLY IS UL LISTED AS A MANUAL TRANSFER SWITCH UNDER UL 1008 (TRANSFER SWITCH STANDARD)
 - STANDARD UNIT IS NON-SWITCHED NEUTRAL. FOR SWITCHED NEUTRAL PLEASE CONSULT FACTORY.
 - FINISH POWDER COATED SERIES W49. SEE TITLE BLOCK FOR COLOR.
 - TYPE 3R CONSTRUCTION
 - NOT FOR INDOOR USE
 - OPTIONAL PLUG KITS AVAILABLE
 - CONDUIT ENTRY AREA SHOWN SHADED
 - FOR AVAILABLE ACCESSORIES & OPTIONS SEE SPEC SHEET
 - FOR SINGLE LINE VISIT WWW.ESLPWR.COM

0	AD	3/27/2023	FOR REFERENCE	
REV.	BY	DATE	DESCRIPTION	
CREATED BY		AD	<div>UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: DECIMALS .x ±.03 .XX ±.01 .XXX ±.005 ANGULAR ± 1/2° BREAK ALL SHARP EDGES .005 - .010 DO NOT SCALE PROPRIETARY THIS DOCUMENT AND THE DATA DISCLOSED HEREIN OR WHEREWITH IS NOT TO BE REPRODUCED, USED OR DISCLOSED IN WHOLE OR IN PART TO ANYONE WITHOUT THE PERMISSION OF ESL.</div> <div><div>CORONA, CALIFORNIA International: +1 (951) 739-7000 Phone: (800) 922-4188 eslpwr.com info@eslpwr.com</div></div>	
SCHEMATIC #:		0901-####		
THICKNESS:		14GA		
MATERIAL:				
FINISH:		WRINKLE GRAY (RAL7035)		
REFERENCE:				
			STORMSWITCH ENCLOSURE RATED 400A	
			DWG NO.	3040-SERIES-A
			REV.	0
			WEIGHT:	400 lbs.
			SHEET 1 of 1	