THIS DOCUMENT AND THE DATA DISCLOSED HEREIN OR WHEREWITH IS NOT TO BE REPRODUCED. USED OR DISCLOSED IN WHOLE OR IN PART TO ANYONE WITHOUT THE PERMISSION OF ESL. NOTES: COMPLETE ASSEMBLY IS UL LISTED AS A TRANSFER SWITCH UNDER UL 1008 (TRANSFER 13.88 ~READYCONNECT" SWITCH STANDARD) 12.50 — 10.50 → LOGO **- 10.50** PRODUCT FINISH POWDER COATED SERIES W49. LABEL STANDARD UNIT IS NON-SWITCHED NEUTRAL. 6.50 SLOTTED FOR SWITCHED NEUTRAL PLEASE CONSULT 1/4 TURN FACTORY. LATCH (3X) NOT FOR INDOOR USE TYPE 3R CONSTRUCTION OPTIONAL PLUG KITS AVAILABLE 36.00 FOAM SEAL INSIDE OF ALL CONDUIT ENTRIES 49.94 DOTTED AREA IS RECOMMENDED CONDUIT 0 **ENTRY AREA** 48.00 HINGED AN GASKETED DOOR READY 0 -PADLOCKABLE HASP DANGER LABEL 30.00 34.00 R.31 (2X) **LEFT VIEW FRONT VIEW RIGHT VIEW** -PHASE A **CONNECT™** PHASE B -PHASE C 10.00 — CAM CONNECTION 3NZT CABLE ENTRY HOLE (5X) **LISTED** 30-400A 480VAC MAX 50/60Hz  $3\phi + N + G$ 10.50 **AUTOMATIC TRANSFER SWITCH** MFG. DATE: ITEM# 3204-001 -NEUTRAL SERIAL#\_ TYPE: 3R -GROUND SUITABLE FOR USE AS SERVICE EQUIPMENT IN THE USA ONLY
SHORT CIRUIT CURRENT RATING IS 30kA; 50kA WITH ABB T5H600 BREAKER OR
200kA CLASS J FUSE UPSTREAM.
COURANT NOMINAL DE COURT-CIRCUIT EST 30kA; 50kA AVEC DISJONCTEUR ABB T5H600 OU
FUSIBLE 200kA CLASSE J EN AMONT
COrona, CA <> (800)922-4188 <> (951)739-7000 <> info@eslpwr.com **BOTTOM VIEW** (CABLE ENTRY HOLES FOR PORTABLE GENERATOR) WEIGHT: 285 400A AUTOMATIC TRANSFER SWITCH GALV STEEL POWER SYSTEMS, INC. 480VAC MAX, 3 PHASE + N + G HICKNESS: WITH CAMS FOR PORTABLE GENERATOR 12 GA CORONA, CALIFORNIA (951) 739-7000 (800) 922-4188 WRINKLE GRAY (RAL 7035) èslpwr.com - info@éslpwr.com 11/15/21 FOR REFERENCE REFERENCE SHEET 1 OF 2 **3204-SERIES** DESCRIPTION C:\ESL Vault\3204\ BY DATE

