



LEFT VIEW

FRONT VIEW

RIGHT VIEW

FRONT VIEW
(DOORS REMOVED)

FRONT VIEW
(DOORS & DEADFRONT REMOVED)

BOTTOM VIEW

ISOMETRIC VIEW

TABLE OF KAIC RATINGS

DISCONNECTS	SHORT CIRCUIT RATING
SWITCH	10 KA
CIRCUIT BREAKER	65KAIC@208VAC
	35KAIC@480VAC
	18KAIC@600VAC

NOTES:

- STANDARD UNIT IS NON-SWITCHED NEUTRAL. FOR SWITCHED NEUTRAL PLEASE CONSULT FACTORY.
- FINISH POWDER COATED SERIES W49. SEE TITLE BLOCK FOR COLOR.
- TYPE 3R CONSTRUCTION
- NOT FOR INDOOR USE
- OPTIONAL PLUG KITS AVAILABLE
- CONDUIT ENTRY AREA SHOWN SHADED
- FOR AVAILABLE ACCESSORIES & OPTIONS SEE SPEC SHEET
- FOR SINGLE LINE VISIT WWW.ESLPWR.COM

PADLOCKABLE
HANDLE COVER

PRODUCT LABEL

HINGED INTERNAL
PROTECTIVE COVER
FOR WIRE OPENING

PHASE ROTATION MONITOR
& FUSES (STANDARD)

DEADFRONT FOR OPERATOR
SAFETY WHILE CONNECTING
AND DISCONNECTING
GENERATOR CABLES

OPERATOR & SAFETY
INSTRUCTIONS

NEUTRAL LUGS

800A DISCONNECT
LABELED
"GENERATOR"

400A, 600V RATED
SINGLE POLE MALE
RECEPTACLES
COLOR CODED:
PER VOLTAGE

G N A B C

GENERATOR FEMALE
PLUG NOT INCLUDED
(SHOWN FOR SCALE
PURPOSES ONLY)



0	AD	4/21/2023	FOR REFERENCE		
REV.	BY	DATE	DESCRIPTION		
CREATED BY		AD	<div>UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES:</div> <div><div>DECIMALS</div><div>ANGULAR</div></div> <div><div>.X ±.03</div><div>± 1/2°</div></div> <div><div>.XX ±.01</div></div> <div><div>.XXX ±.005</div></div> <div><div>BREAK ALL SHARP EDGES</div><div>.005 - .010</div></div> <div><div>DO NOT SCALE</div></div> <div><div>PROPRIETARY</div><div>THIS DOCUMENT AND THE DATA DISCLOSED HEREIN OR WHEREWITH IS NOT TO BE REPRODUCED, USED OR DISCLOSED IN WHOLE OR IN PART TO ANYONE WITHOUT THE PERMISSION OF ESL.</div></div>		
SCHEMATIC #:		0901-####			
THICKNESS:		14GA			
MATERIAL:					
FINISH:		WRINKE FRAY (RAL7035)			
REFERENCE:			<div><div><div>ESL</div><div>CORONA, CALIFORNIA International: +1 (951) 739-7000 Phone: (800) 922-4188 eslpwr.com info@eslpwr.com</div></div><div><div>TEMPTAP</div><div>ENCLSURE RATED 800A</div></div><div><div>DWG NO.</div><div>4680-SERIES-A</div><div>REV.</div><div>0</div></div><div><div>WEIGHT:</div><div>602 lbs.</div><div>SHEET 1 of 1</div></div></div>		