

Safety-interlocked Reefer Outlet Product Selection Information

R32 - 480 - 30 - 22 - S - - D - - SP

Voltage

240 = 240VAC
480 = 480VAC

Circuit Breaker Trip Rating

30 = 30AMP
50 = 50AMP
60 = 60AMP

Circuit Breaker Interrupting Capacity

22 = 22,000 AIC
35 = 35,000 AIC
65 = 65,000 AIC

Receptacle Rating / Configuration

R30 = 30AMP
R32 = 32AMP / IEC 60309-1 & -2 CEE 17 3h
R60 = 60AMP / ISO
R50 = 50AMP

Faceplate Size

S = 5" x 6"
L = 7" x 8"
G = 8" x 9.5"
N = 10.5" x 12"
M = 10" x 10.5"
X = 15" x 21"

Optional Features

Blank = No Options
P = Pilot Light
A = Auxiliary Contact
B = Bell Alarm Contact
R = Rear Actuated

Receptacle Cover

SP = Snap Cover
SW = Screw Cover

Interlock Mechanism Model

C or D = Mechanically Interlocked
E = Electrically Interlocked

Receptacle Material

Blank = Lexan®
N = Polyamide/Rynite Insert
SN = 316 Stainless Steel/Rynite Insert

